



DuPont Chemicals
11102PP



Revised 5-JAN-2005

Printed 2-JUN-2005

"Teflon" Advanced"

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Material Identification

"Teflon" is a registered trademark of DuPont.

Company Identification

MANUFACTURER/DISTRIBUTOR
DuPont
1007 Market Street
Wilmington, DE 19898

PHONE NUMBERS

Product Information	1-800-441-7515 (outside the U.S. 302-774-1000)
Transport Emergency	CHEMTREC 1-800-424-9300(outside U.S. 703-527-3887)
Medical Emergency	1-800-441-3637 (outside the U.S. 302-774-1000)

COMPOSITION/INFORMATION ON INGREDIENTS

Components Material	CAS Number	%
Partially Fluorinated Urethane Co-polymers		4-6
Acrylic Copolymer		4-5
Water	7732-18-5	83-85
Hexylene Glycol	107-41-5	5-6
Non-ionic and Cationic Dispersants		<1

HAZARDS IDENTIFICATION

Potential Health Effects

The product is not a skin or eye irritant when tested in animals. There are inconclusive or unverified reports of

(Continued)

HAZARDS IDENTIFICATION(Continued)

human sensitization to Hexylene Glycol.

Inhalation may cause irritation of the upper respiratory passages with coughing and discomfort.

Ingestion may cause nonspecific discomfort such as nausea, headache, or weakness, heartburn, vomiting, or diarrhea, temporary nervous system depression with anaesthetic effects such as dizziness, headache, confusion, incoordination, and loss of consciousness.

Based on related products, inhalation of spray or mist may cause nasal, throat, or lung irritation. Inhalation of large amounts of respirable particles may be toxic to the lungs. Symptoms may be modest initially, followed in hours by severe shortness of breath requiring prompt medical attention.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

FIRST AID MEASURES**First Aid****INHALATION**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

In case of contact, immediately wash skin with soap and water. Wash contaminated clothing before reuse.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

Notes to Physicians

Activated charcoal mixture may be administered. To prepare activated charcoal mixture, suspend 50 grams activated charcoal in 400 mL water and mix thoroughly. Administer 5 mL/kg, or 350 mL for an average adult.

(Continued)

FIRE FIGHTING MEASURES

Flammable Properties

This material is not expected to have a flash point based on testing done with similar materials.

Hazardous decomposition products including carbon dioxide, carbon monoxide, hydrogen fluoride, toxic gases or particles may be formed during combustion. These products may cause severe eye, nose, throat, and lung irritation or toxic effects.

Extinguishing Media

Water Spray, Foam, Dry Chemical, CO2.

Fire Fighting Instructions

Evacuate personnel to a safe area. Wear self-contained breathing apparatus. Wear full protective equipment.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Spill Clean Up

Soak up with sawdust, sand, oil dry or other absorbent material. Flush away traces with water. Dispose of in an approved container.

HANDLING AND STORAGE

Handling (Personnel)

Avoid breathing vapors or mist. Avoid contact with eyes, skin, or clothing. Wash thoroughly after handling. Wash clothing after use.

Avoid circumstances that produce respirable particles unless suitable ventilation and respirator are used.

Handling (Physical Aspects)

Keep away from heat, sparks and flames.

Storage

Store in a well ventilated place.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use only with adequate ventilation. Avoid breathing mists or spray. Keep away from open flames.

Vent dryer fumes outside work area. Do not aerosolize. In spray applications, use airless type pressure spray equipment at less than 60 psi and exhaust ducts, drip pans

(Continued)

EXPOSURE CONTROLS/PERSONAL PROTECTION(Continued)

or other design features to minimize worker exposure to mists and overspray.

Personal Protective Equipment
EYE/FACE PROTECTION

Wear safety glasses or where splash potential exists wear chemical splash goggles.

RESPIRATORS

Wear NIOSH approved respiratory protection, as appropriate.

PROTECTIVE CLOTHING

Where there is potential for skin contact have available and wear as appropriate impervious gloves, apron, pants and jacket.

Exposure Guidelines
Applicable Exposure Limits

Hexylene Glycol	
PEL (OSHA)	None Established
TLV (ACGIH)	25 ppm, 121 mg/m ³ , Ceiling
AEL * (DuPont)	None Established

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

Exposure Guideline Comments

No AEL has been established for this product. Other products with fluorinated material components have an AEL of 0.1 mg/m³ to 1 mg/m³ (8 hour TWA) for respirable size aerosol particles.

Air monitoring studies conducted at customer sites indicates that the use of the recommended low pressure (less than 60 psi) airless type, garden type or deck specific hand pump sprayer with spray tip orifice minimum of 0.031 inches in diameter does not produce respirable size aerosol particle concentrations near the AEL.

PHYSICAL AND CHEMICAL PROPERTIES**# Physical Data**

Boiling Point	-100 C (-212 F) @ 760 mm Hg
Freezing Point	-0 C (-32 F)
% Volatiles	88-90 WT%
Solubility in Water	Dispersible
pH	7.5-9.2
Odor	Slight, Acrylic
Form	Liquid
Color	White
Specific Gravity	1.01

(Continued)

STABILITY AND REACTIVITY**Chemical Stability**

Stable at normal temperatures and storage conditions.

Incompatibility with Other Materials

None reasonably foreseeable.

Decomposition

Hazardous decomposition products including carbon dioxide, carbon monoxide, hydrogen fluoride, toxic gases or particles may be formed during combustion. These products may cause severe eye, nose, throat, and lung irritation or toxic effects.

Polymerization

Polymerization will not occur.

TOXICOLOGICAL INFORMATION**Animal Data**

Hexylene glycol:

Oral LD50:	3.7 g/kg in rats
Dermal LD50:	7.88 g/kg in rabbits
Inhalation 8 hour ALC:	>18,000 ppm in rats

The product is not a skin irritant and is not an eye irritant when tested in animals.

Hexylene glycol is untested for animal sensitization. Single exposure to Hexylene glycol by ingestion caused hypoactivity, sedation, dyspnea, ataxia, weakness, gastrointestinal inflammation and pneumonitis. Repeated exposure caused increased liver and kidney weights and decreased adrenal weights. No animal data are available to define the carcinogenicity of Hexylene glycol. Animal data show developmental effects only at exposure levels producing other toxic effects in the adult animal. Tests in animals demonstrate no reproductive toxicity. Hexylene glycol does not produce genetic damage in bacterial cell cultures. In mammalian cell cultures it was positive in one test and negative in one test. Hexylene glycol has not been tested in animals for genetic toxicity.

ECOLOGICAL INFORMATION**Ecotoxicological Information**

Hexylene Glycol:

96 hour LC50 - Fathead minnows: 8,690 mg/L

(Continued)

DISPOSAL CONSIDERATIONS**Waste Disposal**

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

TRANSPORTATION INFORMATION**Shipping Information**

Not Regulated as a hazardous material by DOT, IMO, or IATA.

REGULATORY INFORMATION**U.S. Federal Regulations**

TSCA Inventory Status Listed.

TITLE III HAZARD CLASSIFICATIONS SECTIONS 311, 312

Acute : Yes
Chronic : No
Fire : No
Reactivity : No
Pressure : No

OTHER INFORMATION**NFPA, NPCA-HMIS**

NPCA-HMIS Rating

Health	1
Flammability	0
Reactivity	0

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Responsibility for MSDS	MSDS Coordinator
Address	DuPont Chemical Solutions Enterprise
Telephone	Wilmington, Delaware 19898 800-441-7515

Indicates updated section.

End of MSDS